



# BADGER

## Description

Badger is a water borne paint stripper specifically formulated to allow easy removal of uncured water borne paint from walls and floors in the paint booths. The high flash point (none to boiling) makes this a product of choice for the safety conscious. Furthermore the low VOC content (2.1 lbs./gal.) helps your plant meet the strict specifications of the Clean Air Act.

## Features and Benefits

- Can be applied by spray, roll or brush
- Designed to be easily water washable
- Contains no suspect carcinogens
- Clings to walls for complete overspray removal
- Low VOC
- Low Flash Point

## Typical Properties

Appearance	Clear, light yellow liquid
Bulk Density	8.0 lbs/gal
Specific Gravity	0.96 @ 70 °F
Solubility	Soluble
Flash Point	None to boiling
Viscosity	1500 SUS @ 100 °F
V.O.C. Content	2.1 lbs./gal.

## Application Procedure

Badger is used full strength and is normally applied by spray. A brush or roller will work almost as efficiently. Different applications may require different coating thickness'. The recommended thickness of the wet film is from 10 to 20 mil. Once applied, Badger should be left in contact with the overspray for a minimum of five minutes and as long as twenty minutes before rinsing. Good rinsing can be obtained with normal water pressure, however moderate to high-pressure gives the best results.