



E-Z Peel 30

E-Z Peel 30 is a peelable water-based pigmented coating used to coat paint spray booth walls and floors against heavy accumulations of paint overspray. Easily removed, it becomes a temporary barrier to protect many surfaces. The product forms a uniform bright white coating which can be peeled from surfaces in large sheets. E-Z Peel 30 dries very quickly and can be applied by spray, brush or roller.

Features and Benefits

- Can be applied by spray, brush or roller
- Designed to be peeled from walls in large sheets
- Contains no suspect carcinogens
- Clean up with soap and water

Typical Properties

Appearance	White, viscous liquid
Bulk Density	9.3 lbs./gal.
Solubility	Completely water dispersible
Flash Point	None to boiling
V.O.C. Content	Negligible

Application Procedure

E-Z Peel 30 is normally applied by airless spray system using a tip with a large aperture and a moderate angle. The product is applied to a wet film thickness of 5 mils to 15 mils, depending on the application. In general, the thicker the coating the easier the removal. Once applied, E-Z Peel 30 dries to a non-tacky, non-chalky film. The coating remains in place during production hours and is removed after sufficient overspray has deposited. To remove, simply score the film and lift a corner off the wall. The overspray coated film should lift off the wall in large sheets to be disposed of according to government regulations concerning paint waste.