



Hyperstrip

Hyperstrip is a thixotropic solvent based paint stripper specifically formulated to remove the tough new weather resistant clear coatings including 2K isocyanurate coatings. Hyperstrip uses an American Enterprise Industries technology breakthrough to quickly and completely strip paint overspray from walls and floors of the paint booths. This product efficiently strips all other types of automotive finishes including acid resistant clear coats without harsh odors or long contact times.

Features and Benefits

- Can be applied by spray, roll or brush
- Rinses freely with water
- Contains no suspect carcinogens
- Clings to walls for complete overspray removal
- High flash point for safety

Typical Properties

Appearance	Clear, amber liquid
Bulk Density	8.0 lbs/gal
Specific Gravity	0.96 @ 70 °F
Solubility	Emulsifiable
Flash Point	105 °F
Viscosity	400 to 500 cps @ 75 °F
V.O.C. Content	6.8 lbs./gal.
pH (5% emulsion)	10.5

Application Procedure

Hyperstrip is used full strength and is normally applied by spray. A brush or roller will work almost as efficiently. Different applications may require different coating thicknesses. The recommended thickness of the wet film is from 10 to 20 mil. Once applied, Hyperstrip should be left in contact with the overspray for a minimum of five minutes and as long as twenty minutes before rinsing. Good rinsing can be obtained with normal water pressure, however moderate to high pressures and hot water give the best results.

Consult Material Safety Data Sheet for proper handling and storage instructions.