



# Jupiter

Jupiter is a thixotropic solvent based paint stripper specifically formulated to remove the tough new primer coatings. Jupiter uses an American Enterprise Industries technology breakthrough to quickly and completely strip paint overspray from walls and floors of the paint booths. This product efficiently strips other types of automotive finishes without any HAPS or aromatic petroleum solvents.

## Features and Benefits

- Can be applied by spray, roll or brush
- Rinses freely with water
- Contains no suspect carcinogens or HAPS
- Clings to walls for complete overspray removal
- High flash point for safety

## Typical Properties

Appearance	Thick, amber liquid
Bulk Density	7.5 lbs/gal
Specific Gravity	0.9 @ 70 °F
Solubility	Emulsifiable
Flash Point	155 °F
Viscosity	400 to 500 cps @ 75 °F
V.O.C. Content	5.6 lbs./gal.
pH (5% emulsion)	10.5

## Application Procedure

Jupiter is used full strength and is normally applied by spray. A brush or roller will work almost as efficiently. Different applications may require different coating thicknesses. The recommended thickness of the wet film is from 10 to 20 mil. Once applied, Jupiter should be left in contact with the overspray for a minimum of five minutes and as long as twenty minutes before rinsing. Good rinsing can be obtained with normal water pressure, however moderate to high pressures and hot water give the best results.

Consult Material Safety Data Sheet for proper handling and storage instructions.