



# Rainkote WGR

Rainkote WGR is a water resistant solvent based coating used to protect paint booth walls and other surfaces from paint overspray. Rainkote WGR dries quickly to form a white, greasy coating which allows the removal of overspray without the use of solvent based paint strippers. The tackiness of the coating helps to collect airborne dust particles as well as serving to protect the coated surfaces from accumulation paint overspray. Rainkote WGR is ideal for use in galvanized booths as it provides protection from oxidation by water based products.

## Features and Benefits

- Protects galvanized surfaces from oxidation
- Eliminates the need for solvent based strippers
- Can be sprayed for easy application
- High viscosity allows for application of heavy coatings
- Non drying formula remains tacky indefinitely
- Rinses easily with cold water
- Will not interfere with most paint detackification processes
- Bright white color to improve visibility

## Typical Properties

Appearance	White viscous liquid
Bulk Density	7.9 lbs/gal
Solubility	Insoluble
Flash Point	143 °F
Viscosity	5000-8000 cps @ 75 °F

## Application Procedure

Rainkote WGR is normally applied by airless spray but can be applied by brush or roller. The recommended thickness of the wet film is from 5 to 10 mil but varies with the particular application. Good rinsing can be obtained with normal water pressure, however moderate to high pressures give the best results. A thin film may remain after rinsing to provide protection of galvanized surfaces. In some applications with heavy overspray scraping prior to rinsing may be necessary to achieve complete removal.