



## Product Bulletin

# Take Off

Take Off is a thick liquid degreaser and cleaner specially designed for the removal of resinous and tough soils like asphalt, adhesives, grease, oils, sludge, tar, glues, mastics and wet paints. It is also effective for removal of corrosion protective coatings like Dinol and petroleum based rust preventatives. Take Off is a revolutionary natural solvent based product which is biodegradable, nonflammable, low toxic, has a mild agreeable odor with no fumes or vapors and is safe on most plastics and metals. Take Off has much lower VOC levels than other common degreasers and performs with superior detergency and rinsability.

### Features and Benefits

- Contains no chlorinated solvents
- Non-petroleum based product
- Virtually no VOC's
- Nonflammable
- Applicable on all metals surfaces
- Rinses with water; leaves no residue
- Powerful degreaser

### Typical Properties

Appearance	Thick, pale green liquid
Odor	Mild
Bulk Density	8.2 lbs./gals.
Specific Gravity	0.987 @ 70° F
Flash Point	> 300° F
Viscosity	1900 cps
VOC	0.139 lbs per gallon

### Application Procedure

Take Off is used at full strength and is applied by spray, brush or manually wiping. Spot test on plastic to ensure compatibility. Allow Take Off to remain on surface for 30 minutes or more then rinse with water.

Consult Material Safety Data Sheet for a complete description of handling procedures prior to use.